



Tutte le informazioni contenute nella presente scheda tecnica possono essere soggette a modifica senza preavviso.

All information in this datasheet can be changed in any time without notice.

SACET srl Via del Candel 55/D, 32100 Belluno / Italy

info@sacet-probes.com

www.sacet-probes.com

COD. PEGO		S9 N A 10 C EC 30 T P S-v 17 EC = NERO				RIF.	M0.72.01			
SONNTCSPIL90		MOD.								
N°	COMP.	COD.	DESCRIZIONE ITALIANO	COMP.	COD.	ENGLISH DESCRIPTION	Tol.mm	CARATTERISTICHE TECNICHE - TECHNICAL FEATURES		
1	SERIE	S9	SPILLONE NTC PER INFILZARE CON IMPUGNATURA IN ACCIAIO CURVA 90° (2 FILI)	SERIES	S9	PROBE FOR PIERCEING NTC WITH STEELHANDGRIP CURVE 90° (2 WIRES)		CAMPO DI LAVORO OPERATING RANGE	(-50+110)°C	
2	ELEMENTO	N	NTC 10K 1% B3435 1% [9SENNTC020] DISCRETO	ELEMENT	N	NTC 10K 1% B3435 1% [9SENNTC020] DISCRETE		PRECISIONE TOLERANCE	1%	
3	MATERIALE CAP.	A	AISI 304	MATERIAL CASE	A	AISI 304		GRADO DI PROTEZIONE	IP 67	
4	LUNGHEZZA CAP.	10	100 mm.	LENGHT CASE	10	100 mm.	+/- 1.5%	PROTECTION GRADE		
5	Ø CAP.	C	CONICO (DA Ø5,5 - A Ø3,5)	Ø CASE	C	CONICAL (FROM Ø5,5 - TO Ø3,5)	+/- 1.5%	TEMPO DI RISPOSTA RESPONSE TIME	K=5" in liq. V=2m/s	
6	CABLE	EC	GOMMA TERMOPLASTICA (EST) POLIPROP. (INT) [9CAVSAN002]	CABLE	EC	THERMOPLASTIC RUBBER (EST) POLY. (INT) [9CAVSAN002]		COLLAUDI - TESTS		
6A	COLOR		CAVO (NERO) ANIME (NERO-BIANCO)	COLOR		EC	CABLE (BLACK) LEADS (BLACK-WHITE)		TRAZIONE CAVO-CAPSULA TRACTION CABLE-CASE	kg 2/24 h
6B	DIMENSIONI		SEZIONE 2X0.25 MM² Ø3.3 MM	DIMENSIONS		EC	SECTION 2X0.25 MM² Ø3.3 MM	+/- 1%	VALORE RESISTIVO A	25°C 10 Kohm
7	LUNGH.SONDA	30	3 METRI	PROBE LENGHT	30	3 METERS	+/- 3%	OHMIC CHECK		
8	RACCORDO CAVO/CAPSULA	T	TERMORESTRINGENTE 80 mm	CONNECTOR CABLE/CASE	T	THERMOSHRINKING 80 mm		RESISTENZA DI ISOLAMENTO INSULATION DEGREE	20 Mohm 500 Vcc	
9	TERMINALI	P	PUNTALI [9TERVAR007]	TERMINALS	P	PINS [9TERVAR007]		RIGIDITA' DIELECTRIC STRENGTH	2000 Vac	
10	RIEMPITIVO	S	RESINA POLIURETANICA	FILLING	S	POLYURETANIC RESIN		DATE	05/06/2018	
11	OPZIONI	v	PUNTA ACUMINATA - - - - -	OPTIONS	v	NEEDLE TIP - - - - -				
12	EXTRA	17 -	MANICO (170 MM) - -	EXTRAS	17 -	HANDLE (170 MM) - -				