


F27HC *Vantage*

Aeroevaporatori per celle frigorifere
Unit coolers for cold rooms



1450 - 9400 W



4 = 4.5 mm Passo alette Fin spacing			TC > -25 °C					
Modello	Type	F27HC	25-4	36-4	49-4	71-4	107-4	142-4
Potenza (R404A)	• TC 2,5 °C (ΔT1 10K) W		1850	2350	3850	4750	7200	9400
Capacity	TC 0 °C (ΔT1 8K) W		1350	1750	2850	3500	5300	6900
Portata d'aria	Air quantity	m³/h	900	900	1800	1800	2700	3600
Freccia d'aria	Air throw	m	10,5	10,5	12,5	12,5	14,0	15,5
Superficie esterna	External surface	m²	7,3	7,3	14,6	14,6	21,9	29,2
Superficie interna	Internal surface	m²	0,5	0,7	1,0	1,4	2,1	2,8
Peso	Weight	kg	12	13	19	21	28	36
6 = 6.0 mm Passo alette Fin spacing			TC > -25 °C					
Modello	Type	F27HC	19-6	28-6	38-6	55-6	85-6	110-6
Potenza (R404A)	• TC 2,5 °C (ΔT1 10K) W		1600	2050	3300	4150	6300	8300
Capacity	TC 0 °C (ΔT1 8K) W		1200	1500	2440	3050	4650	6100
Portata d'aria	Air quantity	m³/h	950	950	1900	1900	2850	3800
Freccia d'aria	Air throw	m	11,0	11,0	13,0	13	14,5	16,0
Superficie esterna	External surface	m²	5,6	5,6	11,2	11,2	16,8	22,4
Superficie interna	Internal surface	m²	0,5	0,7	1,0	1,4	2,1	2,8
Peso	Weight	kg	11	12	18	20	27	34
7 = 7.0 mm Passo alette Fin spacing			TC > -25 °C					
Modello	Type	F27HC	16-7	23-7	31-7	46-7	70-7	92-7
Potenza (R404A)	• TC 2,5 °C (ΔT1 10K) W		1450	1850	3000	3700	5700	7600
Capacity	TC 0 °C (ΔT1 8K) W		1050	1350	2200	2700	4200	5600
Portata d'aria	Air quantity	m³/h	1000	1000	2000	2000	3000	4000
Freccia d'aria	Air throw	m	11,5	11,5	13,5	13,5	15,5	17,0
Superficie esterna	External surface	m²	4,9	4,9	9,8	9,8	14,7	19,6
Superficie interna	Internal surface	m²	0,5	0,7	1,0	1,4	2,1	2,8
Peso	Weight	kg	10	11	17	19	26	32
DATI COMUNI / COMMON DATA								
Elettroventilatori	Fans	Ø 275 mm x n°	1 0	1 0	2 00	2 00	3 000	4 0000
Assorbimento motori	W		85	85	170	170	255	340
Motor power consumption	1~230 V 50 Hz	A	0,6	0,6	1,2	1,2	1,8	2,4
Assorbimento motori	W		26	26	52	52	78	104
Motor power consumption	EC 1~230 V 50 Hz	A	0,2	0,2	0,4	0,4	0,6	0,8
Sbrinatorio	Defrost	E 230 v	1220	1220	2160	2160	3080	4000
Volume circuito	Circuit volume	dm³	0,8	1,3	1,6	2,3	3,3	4,3
Attacchi entrata	Inlet connections	Ø mm	10	12	12	12	12	12
Attacchi uscita	Outlet connections	Ø mm	10	22	22	28	28	28
Dimensioni	Dimensions	A mm	678	678	1048	1048	1418	1788
		B mm	412	412	782	782	1152	1522

(•) Per altre condizioni vedere diagrammi. (•) For other conditions see diagrams.

EC = Motori con commutazione elettronica (1400 r.p.m.). Risparmio energia = ~ 70%. EC = Motors with electronic commutation (1400 r.p.m.). Energy saving = ~ 70%.

